BATTERY BURNISHER





PE300BU **BATTERY BURNISHER**

shine on.



SteadyOne™ uses advanced fluid drive technology to maintain constant pad pressure and produce more consistent results. Unlike other machines using spring mechanisms that vary when a metal coil compresses or extends, SteadyOne™ automatically adjusts the deck as the pad wears to apply the same pad pressure throughout the burnishing operation. Floor care professionals can now get the same one-pass results today ... and tomorrow.

1 Traction control with dual heavy-duty, 8" (20,3 cm) mark free wheels.

Three (3) 12 volt, 228 AH batteries produce up to 3 hours of run time.

3 On-board battery charger allows operator to plug in anywhere.

Enclosed dust control system (cloth or paper bag) for clean operation.

Unitized roto-molded body with wide area cover panel for easy battery access.

6 Small footprint - only 49" (124 cm) with deck tilted - for compact storage.

Twin rear soft tread 4" (10 cm) caster wheels for a tight turning radius.

Ergonomic handle and controls for comfortable maneuverability.

Quiet (only 67 dBA) 2.5 HP (1.9 kW) electric motor.

10 90-degree tilt deck for easy pad change.

Pad Pressure (%) vs. Time Percentage (%) 100 80 60 Other Battery **Burnishers** 40 20

0

CE approved

The PE300BU keeps 88% of its original pad pressure after 3 hours of burnishing.

Burnish Time

| Dimensions and Performance Specifications | | | | | | | | | | | |
|---|---|-------------------|--------------|----------------|-------------------|--------------------|--------------------|----------------------|---------------------|---------------------|---------------------------------------|
| Burnishing Width | Performance | Pad Size | Pad Speed | Noise Level | Width | Length | | Height | Weight | | Battery Compartment |
| | | | | | | Operating | Storage | | w/batteries | w/o batteries | (w x h x l) |
| 20 in. (51 cm) | 26,400 ft ² /hr (2453 m ² /hr) | 20 in. (51 cm) | 2000 rpm | < 67 db(A) | 22 in. (56 cm) | 58 in. (147 cm) | 49 in. (124 cm) | 41.5 in. (105 cm) | 600 lbs (272 kg) | 260 lbs (118 kg) | 14 x 15 x 21 in. (36 x 38 x 54 cm) |
| 24 in. (61 cm) | 31,200 ft ² /hr (2900 m ² /hr) | 24 in. (61 cm) | 1800 rpm | < 70 db(A) | 26 in. (66 cm) | 61 in. (155 cm) | 49 in. (124 cm) | 41.5 in. (105 cm) | 610 lbs (277 kg) | 270 lbs (123 kg) | 14 x 15 x 21 in. (36 x 38 x 54 cm) |

| PE300BU Model Number | Drive type | Batteries | | |
|-------------------------|--------------------------------|-----------|--|--|
| 300BU20CL | Pad Assist | Lead-Acid | | |
| 300BU20CG | Pad Assist | Sealed | | |
| 300BU20TCL | Traction | Lead-Acid | | |
| 300BU20TCG | Traction | Sealed | | |
| 300BU24CL | Pad Assist | Lead-Acid | | |
| 300BU24CG | Pad Assist | Sealed | | |
| 300BU24TCL | Traction | Lead-Acid | | |
| 300BU24TCG | Traction | Sealed | | |
| Accessories Part Number | Description | | | |
| MP414100 | Cloth dust bag with rubber top | | | |
| MP414200 | Paper dust bag (3 pack) | | | |



Equinox HG™ and other coatings are available for all types of facilities and floor surfaces.



Blue Blend™ and Thermal Thunder™ pads remove scuffs and scratches for a brilliant wet look shine.



White Lightning™ curing pads provide optimum appearance on soft or fresh coatings.

